



| | | | | | | | | | | | | | | | | | | | | | |
|--------------------|--|--|--|------------|---------------|--|------|-----------|------------|-----------------------|------|----------|--|-------|-------|-------|----|------------|--|-------|--|
| | | | | | First Release | | VI.0 | | 2022.06.02 | | Jack | | | | | | | | | | |
| Raytac Corporation | | | | Part Name: | | | | MDBT53-U | | Description | | Revision | | Date | | Name | | Issue | | | |
| Material: | | | | Drawn'd: | | | | RANGE | | COMMON TOLERANCE (MM) | | | | | Unit: | | mm | | | | |
| Treatment: | | | | Quant: | | | | Checked: | | A | | B | | C | | D | | Tolerance: | | A | |
| Part No.: | | | | Approved: | | | | ≤8 | | ±0.05 | | ±0.1 | | ±0.2 | | ±0.4 | | Scale: | | 5: | |
| Drawing No: | | | | D.C.C: | | | | >8~25 | | ±0.08 | | ±0.15 | | ±0.3 | | ±0.6 | | Sheet: | | 1 / 1 | |
| | | | | | | | | >25~80 | | ±0.12 | | ±0.25 | | ±0.5 | | ±1.0 | | | | | |
| | | | | | | | | >80~250 | | ±0.25 | | ±0.4 | | ±0.8 | | ±1.5 | | | | | |
| | | | | | | | | >250~800 | | ±0.5 | | ±0.8 | | ±1.5 | | ±3.0 | | | | | |
| | | | | | | | | >800~2500 | | ±1.0 | | ±1.5 | | ±3.0 | | ±6.0 | | | | | |
| | | | | | | | | ANGULAR | | ±0.15° | | ±0.3° | | ±0.5° | | ±0.8° | | | | | |
| | | | | | | | | | | | | | | | | | | | | | |